

# SHOWER TOILETS VICLEAN

## PRODUCT INFORMATION

### 1 . POSITION



Model	V0E100
Width	385 mm
Depth	595 mm
Weight	34 kg
Description	ViClean-I 100, DirectFlush Sanitary ceramics Power and water connection must be available, Use only in working pressure range between 0.1 Mpa (dynamic) and 1.0 Mpa (static), Use solely in a water temperature range between 10°C and 35°C fastening set included EN 997, EN 1717 with water-saving AQUAREDUCT® system: flush volume 3 / 4,5 litres individual packaging materials composed of: <b>ViClean shower toilet-I 100</b> , 385 x 595 x 400 mm, 220-240 V AC / 50 Hz, incl. remote control, seat with lid Please order compatible toilet element separately.
Flush volume	3 / 4,5 l
Installation	wall-mounted
Outlet	horizontal outlet
Material	Sanitary ceramics
Leed	4
Specification texts	ViClean; - I100; Shower toilet, rimless; ViClean-I 100, DirectFlush; Sanitary ceramics; Size: 385 x 595 mm; Oval; wall-mounted; Power and water connection must be available, Use only in working pressure range between 0.1 Mpa (dynamic) and 1.0 Mpa (static), Use solely in a water temperature range between 10°C and 35°C; Flush volume: 3 / 4,5 l; Leed: 4; fastening set included; EN 997, EN 1717; with water-saving AQUAREDUCT® system: flush volume 3 / 4,5 litres; horizontal outlet; individual packaging materials; Please order compatible toilet element separately.

## COLOURS

White Alpin CeramicPlus	V0E100R1	4051202737573
Glossy Black CeramicPlus	V0E100S0	4051202005245

TECHNICAL DRAWINGS

**V0E100**

